

ROBESON SEWING MACHINE COMPANY

1126 HARPETH IND. CT., FRANKLIN, TENNESSEE 37064 USA

800-422-3330 / 615-790-2222 / 615-791-1241(FAX)

website: www.robessonsew.com / email: robeson@bellsouth.net

SPECIAL OFFERING ON REBUILT



● SPECIFICATIONS

Stitch type	1-needle lockstitch
Sewing size	Max. 190 mm (5-45/64") (L) x 200 mm (7-7/8") (W)
Sewing speed	Max. 2,000 s.p.m. (for stitch length of 2 mm or less)
Stitch length	Max. 10 mm (25/64")
Needle bar stroke	41.2 mm (1-5/8")
Feeding frame lift	(pneumatic type) Max. 30 mm (1-3/16") Standard 22 mm (55/64")
Needle	DP x 5 #14 (standard model)/ DP x 17 (model for heavy-weight material)
Sewing hook	Semi-rotary large hook
Input device	Provided as standard device (can be also connected to the PGM-1 of the compact type programming device)
Memory medium	2DD 3.5-inch micro floppy disk
Number of stitches	176,000 stitches can be stored in a cassette
Number of patterns	44 to 691 patterns can be stored in a cassette (within 4,000 stitches per pattern)
Enlargement/ Reduction	1 to 400 % (increasing or decreasing either the number of stitches or stitch length)
Compressed air	5.5 kg/cm ² 1.8 NI/min.
Power requirements	Single-phase/3-phase (600 VA)
Dimensions	1,090 mm (W) x 1,105 mm (L) x 1,150 (H)
Weight	270 kg

AMS-224B

Sewing size	Max. 145mm (5-45/64")(L) x 400mm(15-3/4")(W)
Enlargement/Reduction	0.1 to 400% (in 0.1% steps)

AMS-222BG•AMS-224BG

Double-capacity shuttle hook	type for heavy-weight materials.
Sewing hook	Special-purpose, double-capacity shuttle hook